

SG2K-S/SG2K5-S/SG3K-S

SUNGROW
Clean power for all

Residential String Inverter



HIGH YIELD

- Industry leading efficiency of 98.2%
- Flexible PV string configurations
- High DC/AC ratio up to 1.3



SMART MANAGEMENT

- Feature-rich online monitoring via App or Web
- Firmware updates & new monitoring features
- Gain energy flow with Sungrow smart meter



SAFE AND RELIABLE


- Built-in surge arresters & RCD
- Cutting-edge technology ensures long life time
- High anti-corrosion rating at C5




EASY INSTALLATION

- Push-in connectors for time-saving installation
- Mounting plate with built-in level
- Fast and easy commissioning via App or LCD

CIRCUIT DIAGRAM



EFFICIENCY CURVE



Type designation	SG2K-S	SG2K5-S	SG3K-S
Input (DC)			
Max. PV input voltage		600 V	
Min. PV input voltage / Startup voltage		90 / 120 V	
Nominal input voltage		360 V	
MPP voltage range		90 V – 560 V	
MPP voltage range for nominal power	210 V – 480 V	260 V – 480 V	310 V – 480 V
No. of MPPTs		1	
Max. number of PV strings per MPPT		1	
Max. PV input current		10 A	
Max. current for input connector		12 A	
Max. PV short-circuit current		12 A	
Output (AC)			
Nominal AC output power	2000 W	2500 W	3000 W
Max. apparent AC output power	2000 VA	2500 VA	3000 VA
Max. AC output current	9.1 A	11.3 A	13.7 A
Nominal AC voltage		230 Vac	
AC voltage range		180 Vac – 276 Vac	
Nominal grid frequency		50 Hz / 60 Hz	
Grid frequency range		45 Hz – 55 Hz / 55 Hz – 65 Hz	
Total Harmonic Distortion (THD)		< 3 % (of nominal power)	
DC current injection		< 0.5 % (of nominal current)	
Power factor		> 0.99 / 0.8 leading – 0.8 lagging	
Feed-in phases / Connection phases		1 / 1	
Efficiency			
Max. efficiency / European efficiency	98.2 % / 97.2 %	98.2 % / 97.5 %	98.2 % / 97.7 %
Protection			
PV reverse connection protection		Yes	
AC short circuit protection		Yes	
Leakage current protection		Yes	
Grid monitoring		Yes	
PV string current monitoring		Yes	
DC switch		Yes	
Overvoltage protection		AC Type II	
General Data			
Dimensions (W*H*D)		300*370*125 mm	
Weight		8.5 kg	
Isolation method		Transformerless	
Ingress protection rating		IP65	
Night power consumption		< 3 W	
Operating ambient temperature range		-25 °C to 60 °C (>45 °C derating)	
Allowable relative humidity (non-condensing)		0 – 100 %	
Cooling method		Natural cooling	
Max. operating altitude		4000 m (> 2000 m derating)	
Display		LCD	
Communication		Wifi / Ethernet (optional)	
DC connection type		MC4 (Max. 6 mm ²)	
AC connection type		Plug and play connector (Max. 6 mm ²)	
Compliance		IEC62109-1, IEC62109-2, IEC62116, IEC61727, EN 61000-6-2, EN 61000-6-3, VDE-AR-N-4105, CEI 0-21, VDE0126-1-1, UTE C15-712, VFR-2014, EN50438, C10/11, G83/2, G59/3	
Compliance		Active & reactive power control, power ramp rate control	
Type designation	SG2K-S	SG2K5-S	SG3K-S

